

Discontinuation Notice of Long-distance right-angle camera cable model FZ-VSL2.

Product Discontinuation

Long-distance right-angle camera cable



Model FZ-VSL2



Recommended Replacement

Long-distance right-angle camera cable

Model FZ-VSL4
(Release at August, 2014)

[Discontinuation date]

The end of December, 2014

[Caution on recommended replacement]

Please confirm the space in the box etc., because the length of the connector in side of the controller is longer than the discontinued one.

[Difference from discontinued product]



Recommended replacement Model	Body Color	Dimen-sions	Wire connection	Mounting Dimensions	Charact-eristics	Operation ratings	Operation methods
FZ-VSL4	**	*	**	-	**	**	-

- ** : Compatible
- * : The change is a little/Almost compatible
- : Not compatible
- : No corresponding specification

[Product Discontinuation and recommended replacement]

Product discontinuation	Recommended replacement
FZ-VSL2	FZ-VSL4

[Body color]

Product discontinuation Model FZ-VSL2	Recommendable replacement Model FZ-VSL4
	

[Cameras / Cables Connection]

Type of camera			Transmission speed select	Product discontinuation Model FZ-VSL2	Recommendable Replacement Model FZ-VSL4
High-speed CMOS cameras *	300,000-pixel	FH-SM/SC	-	Yes	Yes
	2 million-pixel	FH-SM02/SC02	High speed mode	No	No
			Standard mode	Yes	Yes
	4 million-pixel	FH-SM04/SC04	High speed mode	No	No
			Standard mode	Yes	Yes
	12 million-pixel	FH-SM12/SC12	High speed mode	No	No
Standard mode			Yes	Yes	
Digital CCD cameras	300,000-pixel	FZ-S/SC	-	Yes	Yes
	2 million-pixel	FZ-S2M/SC2M	-	Yes	Yes
	5 million-pixel	FZ-S5M2/SC5M2	-	No	No
Small Digital CCD cameras Pen type / flat type		FZ-SF/SFC FZ-SP/SPC	-	-	Yes
High-speed CCD cameras		FZ-SH/SHC	-	Yes	Yes
Intelligent compact CMOS cameras		FZ-SQ[]	-	Yes	Yes

* High-speed CMOS camera is only for the FH series.

[Dimensions]

Product discontinuation Model FZ-VSL2

注1. ケーブル長さは、次の通り
NOTE1. LENGTH OF L IS THE FOLLOWING

仕様 / TYPE	L (mm)
15m	15000 ^{+0.50} ₋₀

Recommendable replacement Model FZ-VSL4

注1. ケーブル長さは、次の通り
NOTE1. LENGTH OF L IS THE FOLLOWING

仕様 / TYPE	L (mm)
15m	15000 ^{+0.50} ₋₀

[Characteristics]

Item	Product discontinuation Model FZ-VSL2	Recommendable replacement Model FZ-VSL4
Shock resistiveness (durability)	10 to 150 Hz single amplitude 0.15 mm 3 directions, 8 strokes, 4 times	
Ambient temperature range	Operation and storage: 0 to 65°C (with no icing or condensation)	
Ambient humidity range	Operation and storage: 40 to 70%RH (with no condensation)	
Ambient atmosphere	No corrosive gases	
Material	Cable sheath, connector: PVC	
Minimum bending radius	93 mm	78 mm
Weight	Approx. 1,600 g	Approx. 1,400 g

Specifications and prices in this product news are as of the issue date and are subject to change without notice.
Only main changes in specifications are described in this document. Please be sure to read the relevant catalogs, datasheets, product specifications, instructions, and manuals for precautions and necessary information when using products.